



Copthorne[®]

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS



BURGUNDY RED



BURNT CLAY



OLD OAK



BASALT



STEEL BLUE



BURGUNDY RED/
BURNT CLAY/OLD OAK
Sold Separately/
Blended on Site

Bundle Type	SINGLE
Thickness (mm)	60MM
Dimension mm	65mm x 200mm x 60mm
Dimension Imperial	2 5/8" x 7 7/8" x 2 3/8"



STANDARD
7 7/8" x 2 5/8" x 2 3/8"
200 x 65 x 60mm

SQFT PER	Bundle	89.20
	Layer	11.15000
	Section	-
	Stone	0.15

PER BUNDLE	Layers	8.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.43
	Section	-
	Layer	15.99
	Bundle	127.95

SAILOR LNFT PER	SqFt	4.41
	Section	-
	Layer	49.21
	Bundle	393.70

UNITS PER	SqFt	6.73
	Section	-
	Bundle	600.00

LBS PER	Layer	294
	Section	-
	Bundle	2,349

ADVANTAGES

REALA™

Cast from historic street pavers

ULTIMA™

Up to 4x stronger than poured-in-place concrete

DRIVE FRIENDLY

Can handle vehicular loads

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting. Please refer to the Polymeric Sand Best Practices on page 91. All measurements are nominal. Contact Unilock for more information.

Internal Use Only. COP ON